



Rite Aid Corporation
830 Planning Schedule with Release Capability
Version 005010

Functional Group ID=**PS**

Introduction:

X12 830 Transaction: Rite Aid Replenishment Forecast By Distribution Center.

This Transaction Set contains the format and establishes the data content of the 'Planning Schedule with Release Capability' as referenced in the X12 Standards.

The X12 830 Transaction of Rite Aid provides a forecast of replenishment demand which can be up to a rolling 10-week period. The transaction is made available on a weekly basis and exchanged every Sunday. The forecast is at the item level for each of the Rite Aid Distribution Centers. Rite Aid shares this data to assist our supply chain trading partners in the ability to achieve complete fulfillment of each Purchase Order.

This is a companion transaction intended to be utilized along with the EDI 852 which contains the inventory position at the item level in each distribution center. The data in these transactions provide the visibility necessary to insure Rite Aid demand is fully supported.

Heading:

| <u>Pos. No.</u> | <u>Seg. ID</u> | <u>Name</u> | <u>Req. Des.</u> | <u>Max.Use</u> | <u>Loop Repeat</u> | <u>Notes and Comments</u> |
|-----------------|----------------|-------------|---|----------------|--------------------|---------------------------|
| M | 0150 | ISA | Interchange Control Header | M | 1 | |
| M | 0175 | GS | Functional Group Header | M | 1 | |
| M | 0100 | ST | Transaction Set Header | M | 1 | |
| M | 0200 | BFR | Beginning Segment for Planning Schedule | M | 1 | |
| LOOP ID - N1 | | | | | 200 | |
| M | 2300 | N1 | Party Identification | M | 1 | |

Detail:

| <u>Pos. No.</u> | <u>Seg. ID</u> | <u>Name</u> | <u>Req. Des.</u> | <u>Max.Use</u> | <u>Loop Repeat</u> | <u>Notes and Comments</u> |
|-----------------|----------------|-------------|----------------------|----------------|--------------------|---------------------------|
| LOOP ID - LIN | | | | | >1 | |
| M | 0100 | LIN | Item Identification | M | 1 | |
| M | 0200 | UIT | Unit Detail | M | 1 | |
| LOOP ID - FST | | | | | >1 | |
| M | 4100 | FST | Forecast Schedule | M | 1 | n1 |
| M | 4200 | SDQ | Destination Quantity | M | 50 | |

Summary:

| <u>Pos. No.</u> | <u>Seg. ID</u> | <u>Name</u> | <u>Req. Des.</u> | <u>Max.Use</u> | <u>Loop Repeat</u> | <u>Notes and Comments</u> |
|-----------------|----------------|-------------|-------------------------|----------------|--------------------|---------------------------|
| M | 0100 | CTT | Transaction Totals | M | 1 | n2 |
| M | 0200 | SE | Transaction Set Trailer | M | 1 | |

| | | | | | |
|---|------|-----|-----------------------------|---|---|
| M | 0300 | GE | Functional Group Trailer | M | 1 |
| M | 0400 | IEA | Interchange Control Trailer | M | 1 |

Transaction Set Notes

1. At least one occurrence of segment FST is required, either in the FST loop or within the SDP loop. These two loops are mutually exclusive.
2. Number of line items (CTT01) is the accumulation of the number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (FST01) for each FST segment.

Segment: **ISA** Interchange Control Header
Position: 0150
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Syntax Notes:

Notes: ISA*00* *00* *01*014578892 *01*RECEIVER
 *180407*1907*<*00501*000001383*0*p*^~

Data Element Summary

| Ref. | Data Des. | Element | Name | Attributes |
|------|-----------|---------|---|--------------|
| M | ISA01 | I01 | Authorization Information Qualifier Code identifying the type of information in the Authorization Information 00 No Authorization Information Present (No Meaningful Information in I02) | M 1 ID 2/2 |
| M | ISA02 | I02 | Authorization Information Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01) | M 1 AN 10/10 |
| M | ISA03 | I03 | Security Information Qualifier Code identifying the type of information in the Security Information 00 No Security Information Present (No Meaningful Information in I04) | M 1 ID 2/2 |
| M | ISA04 | I04 | Security Information This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03) | M 1 AN 10/10 |
| M | ISA05 | I05 | Interchange ID Qualifier Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified 01 Duns (Dun & Bradstreet) | M 1 ID 2/2 |
| M | ISA06 | I06 | Interchange Sender ID Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element 014578892 Rite Aid Duns Number | M 1 AN 15/15 |
| M | ISA07 | I05 | Interchange ID Qualifier Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified | M 1 ID 2/2 |
| M | ISA08 | I07 | Interchange Receiver ID Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them | M 1 AN 15/15 |
| M | ISA09 | I08 | Interchange Date | M 1 DT 6/6 |

| | | | | | | |
|---|-------|-----|--|---|---|--------|
| M | ISA10 | I09 | Date of the interchange Interchange Time Time of the interchange | M | 1 | TM 4/4 |
| M | ISA11 | I65 | Repetition Separator Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator As of ASC X12, version 004030, a repetition separator is required in ISA11. The repetition separator must be non-alphabetic, non-numeric, and not located within data. Repetition Separator "<" | M | 1 | AN 1/1 |
| M | ISA12 | I11 | Interchange Control Version Number Code specifying the version number of the interchange control segments 00501 Standards Approved for Publication by ASC X12 Procedures Review Board through October 2003 | M | 1 | ID 5/5 |
| M | ISA13 | I12 | Interchange Control Number A control number assigned by the interchange sender | M | 1 | N0 9/9 |
| M | ISA14 | I13 | Acknowledgment Requested Code indicating sender's request for an interchange acknowledgment 0 No Interchange Acknowledgment Requested | M | 1 | ID 1/1 |
| M | ISA15 | I14 | Interchange Usage Indicator Code indicating whether data enclosed by this interchange envelope is test, production or information P Production Data | M | 1 | ID 1/1 |
| M | ISA16 | I15 | Component Element Separator Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator Subelement Separator > Element Separator * Segment Terminator ~ | M | 1 | AN 1/1 |

Segment: **GS** Functional Group Header
Position: 0175
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of a functional group and to provide control information
Syntax Notes:
Notes: GS*PS*014578892*RECEIVER*20180407*1907*50075*X*005010~

Data Element Summary

| Ref. | Data Element | Name | Attributes |
|------|--------------|--|-------------|
| M | GS01 | 479 Functional Identifier Code | M 1 ID 2/2 |
| | | Code identifying a group of application related transaction sets PS Planning Schedule with Release Capability (830) | |
| M | GS02 | 142 Application Sender's Code | M 1 AN 2/15 |
| | | Code identifying party sending transmission; codes agreed to by trading partners | |

M

GS03

124

Application Receiver's Code

M

1

AN 2/15

Code identifying party receiving transmission; codes agreed to by trading partners

| | | | | | | |
|---|------|-----|--|---|---|---------|
| M | GS04 | 373 | Date Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year | M | 1 | DT 8/8 |
| M | GS05 | 337 | Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99) | M | 1 | TM 4/8 |
| M | GS06 | 28 | Group Control Number Assigned number originated and maintained by the sender | M | 1 | NO 1/9 |
| M | GS07 | 455 | Responsible Agency Code Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480 X Accredited Standards Committee X12 | M | 1 | ID 1/2 |
| M | GS08 | 480 | Version / Release / Industry Identifier Code Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed 005010 Standards Approved for Publication by ASC X12 Procedures Review Board through October 2003 | M | 1 | AN 1/12 |

Segment: **ST** Transaction Set Header
Position: 0100
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Notes: ST*830*000001169~

Data Element Summary

| Ref. | Data | | | |
|-------------|----------------|-------------|--|------------|
| <u>Des.</u> | <u>Element</u> | <u>Name</u> | <u>Attributes</u> | |
| M | ST01 | 143 | Transaction Set Identifier Code Code uniquely identifying a Transaction Set 830 Planning Schedule with Release Capability | M 1 ID 3/3 |
| M | ST02 | 329 | Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set | M 1 AN 4/9 |

Segment: **BFR** Beginning Segment for Planning Schedule
Position: 0200
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the beginning of a planning schedule transaction set; whether a ship or delivery based forecast; and related forecast envelope dates

Syntax Notes: 1 At least one of BFR02 or BFR03 is required.

Notes: BFR*00*12345 54321**BB*R*20180408*20180428*20180408~

Data Element Summary

| Ref. | Data Element | Name | Attributes |
|------|--------------|---|-------------|
| M | BFR01 | 353 Transaction Set Purpose Code Code identifying purpose of transaction set 00 Original | M 1 ID 2/2 |
| M | BFR02 | 127 Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier | M 1 AN 1/50 |
| M | BFR04 | 675 Schedule Type Qualifier Code identifying the type of dates used when defining a shipping or delivery time in a schedule or forecast BB Customer Production (Consumption) Based | M 1 ID 2/2 |
| M | BFR05 | 676 Schedule Quantity Qualifier Code identifying the type of quantities used when defining a schedule or forecast R Replacement Quantities | M 1 ID 1/1 |
| M | BFR06 | 373 Date Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year Forecast horizon start date | M 1 DT 8/8 |
| M | BFR07 | 373 Date Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year Forecast horizon end date | M 1 DT 8/8 |
| M | BFR08 | 373 Date Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year Date forecast generated | M 1 DT 8/8 |

Segment: **N1** Party Identification

Position: 2300

Loop: N1 Mandatory

Level: Heading

Usage: Mandatory

Max Use: 1

Purpose: To identify a party by type of organization, name, and code

Syntax Notes: 1 At least one of N102 or N103 is required.

2 If either N103 or N104 is present, then the other is required.

Notes: N1*VN**92*54321~

Data Element Summary

| Ref. | Data Element | Name | Attributes |
|------|--------------|--|------------|
| M | N101 | 98 Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual VN Vendor | M 1 ID 2/3 |
| M | N103 | 66 Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) | M 1 ID 1/2 |

| | | | | | | | |
|---|------|----|--|------------------------------------|---|---|---------|
| M | N104 | 67 | 92 | Assigned by Buyer or Buyer's Agent | M | 1 | AN 2/80 |
| | | | Identification Code | | | | |
| | | | Code identifying a party or other code | | | | |
| | | | Vendor Number Assigned by Rite Aid | | | | |

Segment: **LIN** Item Identification
Position: 0100
Loop: LIN Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify basic item identification data
Syntax Notes:

- 1 If either LIN04 or LIN05 is present, then the other is required.
- 2 If either LIN06 or LIN07 is present, then the other is required.
- 3 If either LIN08 or LIN09 is present, then the other is required.
- 4 If either LIN10 or LIN11 is present, then the other is required.
- 5 If either LIN12 or LIN13 is present, then the other is required.
- 6 If either LIN14 or LIN15 is present, then the other is required.
- 7 If either LIN16 or LIN17 is present, then the other is required.
- 8 If either LIN18 or LIN19 is present, then the other is required.
- 9 If either LIN20 or LIN21 is present, then the other is required.
- 10 If either LIN22 or LIN23 is present, then the other is required.
- 11 If either LIN24 or LIN25 is present, then the other is required.
- 12 If either LIN26 or LIN27 is present, then the other is required.
- 13 If either LIN28 or LIN29 is present, then the other is required.
- 14 If either LIN30 or LIN31 is present, then the other is required.

Notes: LIN**IN*0306130*UI*01182236130~

Data Element Summary

| Ref. | Data Des. | Data | | Attributes | |
|------|-----------|---------|--|------------|-----------|
| | | Element | Name | | |
| M | LIN02 | 235 | Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) IN Buyer's Item Number | M | 1 ID 2/2 |
| M | LIN03 | 234 | Product/Service ID Identifying number for a product or service | M | 1 AN 1/48 |
| M | LIN04 | 235 | Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) UA U.P.C./EAN Case Code (2-5-5) UI U.P.C. Consumer Package Code (1-5-5) VN Vendor's (Seller's) Item Number | M | 1 ID 2/2 |
| M | LIN05 | 234 | Product/Service ID Identifying number for a product or service | M | 1 AN 1/48 |

Segment: **UIT** Unit Detail
Position: 0200
Loop: LIN Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify item unit data
Syntax Notes: 1 If UIT03 is present, then UIT02 is required.
Notes: UIT*PC~

Data Element Summary

| Ref. | Data Element | Name | Attributes |
|------|--------------|--|------------|
| M | UIT01 | C001 Composite Unit of Measure | M 1 |
| | | To identify a composite unit of measure (See Figures Appendix for examples of use) | |
| M | C00101 | 355 Unit or Basis for Measurement Code | M ID 2/2 |
| | | Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken | |
| | | PC Piece | |

Segment: **FST** Forecast Schedule
Position: 4100
Loop: FST Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify the forecasted dates and quantities
Syntax Notes: 1 If either FST06 or FST07 is present, then the other is required.
 2 If either FST08 or FST09 is present, then the other is required.
 3 If FST13 is present, then FST12 is required.
Notes: FST*768*D*F*20180408*20180414~

Data Element Summary

| Ref. | Data Element | Name | Attributes |
|------|--------------|--|------------|
| M | FST01 | 380 Quantity | M 1 R 1/15 |
| | | Numeric value of quantity | |
| M | FST02 | 680 Forecast Qualifier | M 1 ID 1/1 |
| | | Code specifying the sender's confidence level of the forecast data or an action associated with a forecast | |
| | | D Planning | |
| M | FST03 | 681 Timing Qualifier | M 1 ID 1/1 |
| | | Code specifying interval grouping of the forecast or product activity | |
| | | F Flexible Interval (from Date X through Date Y) | |
| M | FST04 | 373 Date | M 1 DT 8/8 |
| | | Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year | |
| | | Beginning day | |
| M | FST05 | 373 Date | M 1 DT 8/8 |
| | | Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year | |

Segment: **SDQ** Destination Quantity
Position: 4200
Loop: FST Mandatory
Level: Detail
Usage: Mandatory
Max Use: 50
Purpose: To specify destination and quantity detail
Syntax Notes:

- 1 If either SDQ05 or SDQ06 is present, then the other is required.
- 2 If either SDQ07 or SDQ08 is present, then the other is required.
- 3 If either SDQ09 or SDQ10 is present, then the other is required.
- 4 If either SDQ11 or SDQ12 is present, then the other is required.
- 5 If either SDQ13 or SDQ14 is present, then the other is required.
- 6 If either SDQ15 or SDQ16 is present, then the other is required.
- 7 If either SDQ17 or SDQ18 is present, then the other is required.
- 8 If either SDQ19 or SDQ20 is present, then the other is required.
- 9 If either SDQ21 or SDQ22 is present, then the other is required.

Notes: SDQ*EA*92*00010*768*00035*0*00081*0~

More than one SDQ segment may be sent for each forecast schedule sent in an FST segment.

Data Element Summary

| Ref. | Des. | Data Element | Name | Attributes |
|------|-------|--------------|---|-------------|
| M | SDQ01 | 355 | Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken EA Each | M 1 ID 2/2 |
| M | SDQ02 | 66 | Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) 92 Assigned by Buyer or Buyer's Agent | M 1 ID 1/2 |
| M | SDQ03 | 67 | Identification Code Code identifying a party or other code | M 1 AN 2/80 |
| M | SDQ04 | 380 | Quantity Numeric value of quantity | M 1 R 1/15 |
| | SDQ05 | 67 | Identification Code Code identifying a party or other code | X 1 AN 2/80 |
| | SDQ06 | 380 | Quantity Numeric value of quantity | X 1 R 1/15 |
| | SDQ07 | 67 | Identification Code Code identifying a party or other code | X 1 AN 2/80 |
| | SDQ08 | 380 | Quantity Numeric value of quantity | X 1 R 1/15 |
| | SDQ09 | 67 | Identification Code Code identifying a party or other code | X 1 AN 2/80 |
| | SDQ10 | 380 | Quantity Numeric value of quantity | X 1 R 1/15 |
| | SDQ11 | 67 | Identification Code Code identifying a party or other code | X 1 AN 2/80 |
| | SDQ12 | 380 | Quantity Numeric value of quantity | X 1 R 1/15 |

| | | | | | |
|-------|-----|--|---|---|---------|
| SDQ13 | 67 | Identification Code Code identifying a party or other code | X | 1 | AN 2/80 |
| SDQ14 | 380 | Quantity Numeric value of quantity | X | 1 | R 1/15 |
| SDQ15 | 67 | Identification Code Code identifying a party or other code | X | 1 | AN 2/80 |
| SDQ16 | 380 | Quantity Numeric value of quantity | X | 1 | R 1/15 |
| SDQ17 | 67 | Identification Code Code identifying a party or other code | X | 1 | AN 2/80 |
| SDQ18 | 380 | Quantity Numeric value of quantity | X | 1 | R 1/15 |
| SDQ19 | 67 | Identification Code Code identifying a party or other code | X | 1 | AN 2/80 |
| SDQ20 | 380 | Quantity Numeric value of quantity | X | 1 | R 1/15 |
| SDQ21 | 67 | Identification Code Code identifying a party or other code | X | 1 | AN 2/80 |
| SDQ22 | 380 | Quantity Numeric value of quantity | X | 1 | R 1/15 |

Segment: CTT Transaction Totals
Position: 0100
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To transmit a hash total for a specific element in the transaction set
Syntax Notes: 1 If either CTT03 or CTT04 is present, then the other is required.
2 If either CTT05 or CTT06 is present, then the other is required.
Notes: CTT*2~

Data Element Summary

| Ref. | Data | | | Attributes |
|-------------|----------------|-------------|--|------------|
| <u>Des.</u> | <u>Element</u> | <u>Name</u> | | |
| M | CTT01 | 354 | Number of Line Items Total number of line items in the transaction set | M 1 NO 1/6 |

Segment: SE Transaction Set Trailer
Position: 0200
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)
Syntax Notes:

Data Element Summary

Ref. Data

| | <u>Des.</u> | <u>Element</u> | <u>Name</u> | <u>Attributes</u> |
|---|-------------|----------------|--|-------------------|
| M | SE01 | 96 | Number of Included Segments Total number of segments included in a transaction set including ST and SE segments | M 1 NO 1/10 |
| M | SE02 | 329 | Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set | M 1 AN 4/9 |

Segment: **GE** Functional Group Trailer
Position: 0300
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of a functional group and to provide control information
Syntax Notes:

Data Element Summary

| | <u>Ref.</u> | <u>Data Element</u> | <u>Name</u> | <u>Attributes</u> |
|---|-------------|---------------------|--|-------------------|
| M | GE01 | 97 | Number of Transaction Sets Included Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element | M 1 NO 1/6 |
| M | GE02 | 28 | Group Control Number Assigned number originated and maintained by the sender | M 1 NO 1/9 |

Segment: **IEA** Interchange Control Trailer
Position: 0400
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments
Syntax Notes:

Data Element Summary

| | <u>Ref.</u> | <u>Data Element</u> | <u>Name</u> | <u>Attributes</u> |
|---|-------------|---------------------|--|-------------------|
| M | IEA01 | I16 | Number of Included Functional Groups A count of the number of functional groups included in an interchange | M 1 NO 1/5 |
| M | IEA02 | I12 | Interchange Control Number A control number assigned by the interchange sender | M 1 NO 9/9 |

Sample Data

ISA*00* *00* *01*014578892 *01*RECEIVER *180407*1907*00501*000001383*0*P*^~
GS*PS*014578892*RECEIVER*20180407*1907*50075*X*005010~
ST*830*000001169~
BFR*00*07437 33672**BB*R*20180327*20180625*20180327~
N1*VN**92*33672~
LIN**IN*0306130*UI*01182236130~
UIT*PC~
FST*2736*D*F*20180327*20180402~
SDQ*EA*92*00010*864*00029*288*00035*240*00050*0*00053*336*00054*288*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*720~
FST*432*D*F*20180403*20180409~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*432*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*1488*D*F*20180410*20180416~
SDQ*EA*92*00010*864*00029*288*00035*0*00050*0*00053*0*00054*0*00055*0*00056*336*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*1872*D*F*20180417*20180423~
SDQ*EA*92*00010*0*00029*0*00035*240*00050*0*00053*336*00054*288*00055*0*00056*0*00080*0*00081*288~
SDQ*EA*92*00088*720~
FST*720*D*F*20180424*20180430~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*432*00056*0*00080*288*00081*0~
SDQ*EA*92*00088*0~
FST*3264*D*F*20180501*20180507~
SDQ*EA*92*00010*864*00029*288*00035*240*00050*192*00053*336*00054*0*00055*0*00056*336*00080*0*00081*288~
SDQ*EA*92*00088*720~
FST*288*D*F*20180508*20180514~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*288*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*2160*D*F*20180515*20180521~
SDQ*EA*92*00010*864*00029*288*00035*0*00050*0*00053*0*00054*0*00055*432*00056*336*00080*240*00081*0~
SDQ*EA*92*00088*0~
FST*2064*D*F*20180522*20180528~
SDQ*EA*92*00010*0*00029*0*00035*240*00050*192*00053*336*00054*288*00055*0*00056*0*00080*0*00081*288~
SDQ*EA*92*00088*720~
FST*720*D*F*20180529*20180604~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*432*00056*0*00080*288*00081*0~
SDQ*EA*92*00088*0~
FST*3024*D*F*20180605*20180611~
SDQ*EA*92*00010*864*00029*288*00035*0*00050*192*00053*336*00054*0*00055*0*00056*336*00080*0*00081*288~
SDQ*EA*92*00088*720~
FST*528*D*F*20180612*20180618~
SDQ*EA*92*00010*0*00029*0*00035*240*00050*0*00053*0*00054*288*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*2448*D*F*20180619*20180625~

SDQ*EA*92*00010*816*00029*288*00035*0*00050*0*00053*336*00054*0*00055*432*00056*336*00080*24
0*00081*0~
SDQ*EA*92*00088*0~
LIN**IN*0330294*UI*01182230294~
UIT*PC~
FST*0*D*F*20180327*20180402~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180403*20180409~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180410*20180416~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180417*20180423~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180424*20180430~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180501*20180507~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180508*20180514~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180515*20180521~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180522*20180528~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180529*20180604~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180605*20180611~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180612*20180618~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
FST*0*D*F*20180619*20180625~
SDQ*EA*92*00010*0*00029*0*00035*0*00050*0*00053*0*00054*0*00055*0*00056*0*00080*0*00081*0~
SDQ*EA*92*00088*0~
CTT*2~
SE*87*000001169~
GE*1*50075~
IEA*1*000001383~

General Comments

- “Rite Aid’s DUNS+4 /Distribution Centers: The link contained in these guidelines will provide listing of all Rite Aid DC ship-to-locations addresses and phone number , DEA number, DUNS+4 number and preferred LTL carrier. Also indicated if applicable will be any satellite location of the primary DC ” DC listings can be downloaded at <http://www.riteaidediservices.com/distribution-centers/>

Guidelines for Functional Acknowledgements

- Upon receipt of any EDI transaction, the receiving partner shall promptly and properly transmit a Functional Acknowledgement (ANSI ASC X12 997).
- Rite Aid expects that trading partners pick up on a daily basis and acknowledge by returning the Functional Acknowledgement within 24 hours of the time Rite Aid transmitted the original document.
- The receiving partner is expected to monitor and review all 997s for errors that may require attention.